

CODEPROX-N reader for Nexa aluminium panel



Reference: N3000/CODEPROX-N

Product code: 20700017

EAN code: 8429898025834



Main characteristics

CODEPROX-N reader assembled on special N3000 adapter module.

- 125KHz waterproof proximity and keypad reader with Wiegand 26 technology
- For IP OPENER Wiegand controllers or stand-alone operation
- Capacity for up to 1000 users
- Admits PROKEY ID and TAGKEY ID cards and fobs
- Three contact output relay (C, NO and NC)
- IP66 degree of protection
- In stand-alone mode requires 12Vdc power supply

Dimensions: 100(W) x 100(H) mm

More information

Specifications	
Technology	wiegand
Type Function	Standalone,Slave
Reading / Detection Type	PIN,Proximity
RFID Frequency (KHz)	125
RFID Reading /coverage distance (cm)	6
Use	Outdoor,Indoor
Max. Users	990
Mounting	Embedded
Relay contacts	Yes
Incorporates base	Yes
State LEDs	Yes
Degree of protection (IP)	66
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-40
Dimensions - High (mm)	62
Dimensions - Width (mm)	48
Dimensions - Deep (mm)	25
Weight (gr.)	289

Accessories

- PROKEY ID proximity card
- TAGKEY ID proximity key fob
- PSU-121B 12Vdc / 1.3A power supply

Visit in the website: <https://golmar.es/products/n3000-codeprox-n>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Visit in the website: <https://golmar.es/products/n3000-codeprox-n>