

KEYBUS SE keypad and proximity reader



Reference: KEYBUS SE
Product code: 20720001
EAN code: 8429898024448



Main characteristics

- Keypad with dual proximity reader and Wiegand 26 technology
- For IP OPENER controllers or **standalone operation**
- Capacity for 2000 users
- Dual frequency band (13.56MHz and 125KHz)
- Compatible with cards and keyfobs: CARDDOOR MF+, TAGDOOR MF+, ISOPROX, KEYPROX (13,56MHz), PROKEY ID and TAGKEY ID (125KHz)
- Three-contact output relay (C, NO and NC)
- Wall installation with IP68 protection rating
- Stand-alone mode requires 12Vdc power supply.

Dimensions: 83(W) x 170(H) x 26(D) mm

More information

Specifications	
Technology	wiegand
Type Function	Standalone,Slave
Reading / Detection Type	PIN,Proximity
RFID Frequency (KHz)	125
RFID Frequency (MHz)	13.56
RFID Reading /coverage distance (cm)	2
Use	Outdoor,Indoor
Max. Users	2000
Mounting	Surface
Signaling	Led
Relay contacts	Yes
Incorporates base	Yes
State LEDs	Yes
Input voltage	12Vdc
Degree of protection (IP)	68
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-20
Dimensions - High (mm)	170
Dimensions - Width (mm)	83
Dimensions - Deep (mm)	26
Weight (gr.)	610

Accessories

- CARDDOOR MF+ Mifare Plus Proximity Card
- ISOPROX proximity card
- TAGKEY ID proximity key fob
- TAGDOOR MF+ Mifare Plus proximity keyfob
- PROKEY ID proximity card
- PSU-121B 12Vdc / 1.3A power supply

Visit in the website: <https://golmar.es/products/keybus-se>

Visit in the website: <https://golmar.es/products/keybus-se>