

Reference: EASYGATE
Product code: 20740440
EAN code: 8429898021089



Main characteristics

EASYGATE controller

- Proprietary 2SAFE protocol
- Local programming and via web environment
- RFID verification
- Up to 2000 users (web environment) or 1500 (local mode)
- 12/24VAC or DC power supply (not included)

Dimensions: 70(W) x 70(H) x 19(D) mm

More information

Specifications	
Technology	2SAFE
No. of doors	1
Communication	Communication protocol: proprietary (2SAFE)
Reading/management type	Proximity
Use	Indoor
RFID Frequency (MHz)	13.56
Max. Users	2000
Requires a license	No
Format Reports	XLS
Report generation	Yes
Input voltage	12Vdc,12Vac,24Vdc,24Vac
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-20
Dimensions - High (mm)	70
Dimensions - Width (mm)	70
Dimensions - Deep (mm)	19
Weight (gr.)	115

Accessories

- GM-IPOP 80 proximity and Bluetooth wall-mounted reader
- GM-IPOP CHAMP proximity reader
- GM-MRIPOP proximity wall reader MIFARE+ for IPOP controllers
- GM-ORIPOP Vandal-proof wall reader for GM-IPOP control panels
- EL4500/EASY electronic proximity module
- GM-IPOP 40 proximity and Bluetooth wall-mounted reader
- MR-V2 proximity reader-circuit with 2SAFE technology
- GM-SRIPOP proximity wall reader MIFARE+ for IPOP controllers
- GM-USBIPOP USB programmer for EasyGate and IP Opener controllers
- TF-104 transformer

Visit in the website: <https://golmar.es/products/easygate>

Visit in the website: <https://golmar.es/products/easygate>