

TEST-MINI analogue / IP installer Monitor

Reference: TEST-MINI
Product code: 31690998
EAN code: 8429898025780



Main characteristics

- Analogue and IP test monitor
 - Compatible with high resolution 4K
 - Analogue cameras (AHD, CVI, TVI) and CVBS.
 - Compatible with IP cameras up to 4K
 - 4" touch screen display with 800 x 480 resolution
 - Camera control via UTC
 - Auto detection of IP cameras
 - Built-in PoE port
 - Cable tester
 - 8h battery life with normal use

More information

Display	4" touch screen
Screen resolution	800 x 480
Maximum analogue resolution	3840 x 2160, 8Mpx (4K)
Maximum IP resolution	3840 x 2160, 8Mpx (4K)
Power output	12V / 3A for analogue camera setup and focus
PoE output	48V PoE for IP camera focus and adjustment
UTP cable test	On-screen cable status
DTR cable test	Pair status, length, attenuation, impedance. Maximum 180m
IP camera test	IP Discovery, Quick ONVIF, IPC Test, RTSP Play
UTC control	Yes (PTZ and OSD)
Network port	10/100/1000M, RJ45 connector
Network test	Trace route, link, DHCP server, ping
Audio test	1 audio input
Wifi	Built in, 150Mbps
Internal battery	7,4V, 2400mAh lithium battery
Charging time	4h
Battery life	8h
Languages	English, Spanish, Portuguese, Italian, Italian, French, Polish, German, Turkish, Korean
Auto power off	1 - 30 min
Operating temperature	-10/+50°C
Operating humidity	30/90%
Power supply	12Vdc / 1A power supply included
Dimensions	126 (W) x 82 (H) x 32 (D) mm
Weight	320 g

Visit in the website: <https://golmar.es/products/test-mini>

Visit in the website: <https://golmar.es/products/test-mini>