

CIP-21D5E PoE dome IP camera, 5Mpx

Reference: CIP-21D5E
 Product code: 31691027
 EAN code: 8429898018508



Main characteristics

- Dome with 2.8mm lense 5Mpx PoE
- 1/2.7" Progressive CMOS Sensor
- Compression H.265 / H.264
- Owner protocol / Onvif 2.6
- Fixed optics 2.8mm / 92° field of view
- 18 leds (SMD) / 30m
- Degree of protection IP66
- Dimensions 60(W) x 90(H) x 100(D)mm

Additional information

Resolution	5MP 2592(H)×1944(V)	System Compatibility	ONVIF(Ver 2.6)
Image Sensor	1/2.7" Progressive CMOS	Interface	RJ45 10M / 100M Ethernet interface x1
Min. Illumination	Color 0.05lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	Led	18pcs(SMD)
Shutter	1/5 ~ 1/20000s	IR Range	Up to 30m
Slow shutter	Support	SD storage	no
Lens	2.8 mm H.FOV: 92°	Alarm Trigger	no
Day & Night	IR cut filter with auto switch	Audio	no
WDR	Digital WDR	Video Output:	no
Video Compression	H.265/H.264	Reset Button	no
Video bit rate	256Kbps ~ 8Mbps	PoE	yes
Stream	Dual	Water Proof	IP 66
	Mainstream (1~15fps)	Power Supply	DC 12V/POE
	5MP(2592×1944),4MP(2592×1520)	Consumption	≤ 7W
Frame Rate	3MP(2048×1520),1080P(1920×1080)	Dimension	60x 90x100mm
	960P(1280×960), 720P(1280×720)	Weight	appr. 225g
	Substream (1~15fps)	Storage Temperature	-30 +60°C
	VGA(640×480),QVGA(320×240)	Operating Temperature	-30 +55°C
Image Settings:	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable		
BLC	Support		
Privacy Mask	Support		
Video Analytics	N/A		
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,		

Accessories

- C-BASE01 high base for camera
- C-BASE02 high base for camera
- SW-104 4-port PoE Switch

Visit in the website: <https://golmar.es/products/cip-21d5e>