

Dome IP camera CIP-24D8FA Full color 2.8-12mm motorized. VA 8MPX



Reference: CIP-24D8FA
Product code: 31691033
EAN code: 8429898026152



Main characteristics

- 1/2.7" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif (S/G/T profile)
- 2.8 to 12mm autofocus motorised lense
- 111° to 36° horizontal angle of view
- Advanced video analytics (perimeter, line of sight, pedestrian, vehicle, face detection, crowd and queue detection...)
- 30m range infrared illumination
- White light illumination with a range of 25m
- IP67 degree of protection
- Micro SD card slot
- Audio, reset and alarm terminals
- Power-Out function
- Compatible with sockets C-BASE02 and C-BASE04
- Dimensions: 135(Ø) x 120(D) mm

More information

Visit in the website: <https://golmar.es/products/cip-24d8fa>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Dome IP camera CIP-24D8FA Full color 2.8-12mm motorized. VA 8MPX



Specifications	
Type	Dome
Technology	IP
Image sensor	1/2,7" progressive CMOS
Max. Resolution	8Mpx
Colour	White
Mounting	Ceiling
Lense	Motorized
Focal length	2,8 - 12 mm
Zoom (x)	4
Max. Aperture ratio	F1,2
Horizontal field of view (°)	113(W) - 36(T)°
Vertical field of view (°)	59(W) - 20(T)°
Minimum illumination (lux)	Color 0.007lux @ F1.0(AGC ON) ; B/N 0 lux @ IR ON
Night vision mode	Full Color
White light distance (m)	25
IR distance max. (m)	30
Additional functions	AWB,BLC,AES,3D-DNR,D-WDR
Bitrate	256Kbps ~ 16Mbps
Main Stream (FPS)	25fps @ 8MP(3840x2160), 5MP(2592x1944), 4MP(2592x1520),3MP(2304x1296),1080P(1920x1080), 960P(1280*960), 720P(1280x720)
Sub Stream (FPS)	25 fps @ 720P(1280x720), VGA(640x480), QVGA(320x240)
Video compression	H.264,H.265
Video Analysis	LCD,PID,PD,VD,FD,SOD,CC,CD,QD,HM
Internal storage	Yes (max 256Gb)
Built-in microphone	No
Built-in speaker	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Degree of protection (IP)	67
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-35
Relative humidity work (max.)	95%
Input voltage (V)	12Vcc,PoE
Included power supply	No
Dimensions - Diameter (mm)	135
Dimensions - Deep (mm)	120
Weight (gr.)	829
Certifications	CE, RoHS

Accessories

- C-BASE02 high junction box for camera
- C-BASE04 high junction box for camera

Visit in the website: <https://golmar.es/products/cip-24d8fa>