

Reference: CIP-24D2MA2
 Product code: 31691065
 EAN code: 8429898022758



Main characteristics

- Dome with video analysis and motorized optics 2Mpx
- 1/2.8" Progressive CMOS Sensor
- 2.8-12mm motorized autofocus optics
- Field of view 109° - 32°
- Compression H.264 / H.265
- Owner protocol / Onvif 2.6
- Advanced video analysis (perimeter, crossing line, stationary object, pedestrian detection, face detection, counter)
- 40 leds (SMD) / 40m
- Degree of protection IP66
- With audio terminal, reset, alarm, video output
- Dimensions 135 (Ø) x 120(P)mm
- Power supply 12Vcc / PoE

Resolution	2MP 1920(H)×1080(V)	Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
Image Sensor	1/2.8" Progressive CMOS (OV12895)	System Compatibility	ONVIF(Ver 2.6, Profile S, Profile G)
Min. Illumination	Color 0.01lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON	Interface	RJ45 10M / 100M Ethernet interface x1
Shutter	1/5 ~ 1/20000s	Led	40pcs(SMD)
Lens	2.8 ~ 12mm (Motorized) H.FOV: 109 ~ 32°	IR Range	Up to 40m
F No.	F No. W:1.6--T:2.9±5%	SD storage	yes Micro SD/SDHC/SDXC slot, up to 128 GB
Day & Night	IR cut filter with auto switch	Alarm Trigger	1 input / 1 output
WDR	120 dB	Audio	1 input / 1 output (RCA)
Video Compression	H.264/H.265	Video Output:	yes
Video bit rate	256Kbps ~ 12Mbps	Reset Button	yes
Triple Stream	yes	PoE	yes
	Mainstream default 30fps	Water Proof	IP 66
	1080P(1920x1080), 720P(1280x720),	Power Supply	DC 12V/POE
	Substream default 30fps)	Consumption	≤ 9W
Resolution	1080P(1920x1080),720P(1280x720),VGA(640x480),	Dimension	Ø135.4 X 86mm
	QVGA(320x240)	Weight	appr.
	Mobilestream default 10fps	Storage Temperature	-30 +60°C
	VGA(640x480), QVGA 320x240	Operating Temperature	-30 +55°C
Image Settings:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, Hue adjustable		
BLC	Support		
ROI	Support		
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Face Detection(DEEP LEARNING), Cross Counting.		

Accessories

- C-BASE02 high base for camera
- C-BASE04 high dock for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications
- SW-104 4-port PoE Switch

Visit in the website: <https://golmar.es/products/cip-24d2ma2>