

Dome IP camera CIP-24D5FA Full color 2.8-12mm motorized VA 5Mpx



Reference: CIP-24D5FA
Product code: 31691069
EAN code: 8429898025827



Main characteristics

- 1/2.7" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif (S/G/T profile)
- 2.8 to 12mm autofocus motorized lense
- 112° to 35° horizontal viewing angle
- Advanced video analytics (perimeter, line of sight, pedestrian and face detection
- crowd and queue detection...)
- Infrared illumination with 30m range
- IP66 protection rating
- Micro SD card slot
- Audio, reset and alarm terminals
- Power-Out function
- Compatible with C-BASE02 and C-BASE04 sockets
- Dimensions: 135(Ø) x 120(H) mm

More information

Visit in the website: <https://golmar.es/products/cip-24d5fa>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Dome IP camera CIP-24D5FA Full color 2.8-12mm motorized VA 5Mpx



Specifications	
Type	Dome
Technology	IP
Image sensor	1/2,7" progressive CMOS
Max. Resolution	5Mpx
Colour	White
Mounting	Ceiling
Lense	Motorized
Focal length	2.8-12mm
Zoom (x)	4
Horizontal field of view (°)	112
Minimum illumination (lux)	Color 0.05lux @ F1.2(AGC ON)
Night vision mode	Full Color
White light distance (m)	25
IR distance max. (m)	30
WDR	Yes
Additional functions	AWB,BLC,AES,3D-DNR
Bitrate	128Kbps ~ 8Mbps
Video compression	H.264,H.265
Face recognition	No
Video Analysis	LCD,PID,PD,VD,FD,SOD,CC,CD,QD,HM
Internal storage	Yes (max 256Gb)
Network interface	RJ45
I / O alarms	1/1
I / O audio	1/1
Built-in microphone	No
Built-in speaker	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Degree of protection (IP)	IP66
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-30
Input voltage (V)	12Vcc,PoE
Included power supply	No
Max. consumption (W)	11.23
Dimensions - High (mm)	120
Dimensions - Diameter (mm)	135
Weight (gr.)	854
Certifications	CE,RoHS

Accessories

- Wall mount bracket SP-24P for dome
- C-BASE04 high junction box for camera
- SW-104 4-port PoE Switch
- C-BASE02 high junction box for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications

Visit in the website: <https://golmar.es/products/cip-24d5fa>