

Bullet IP camera CIP-24B5DA Full color bullet 2.8-12 motorized VA AD 5Mpx



Reference: CIP-24B5DA
Product code: 31691070
EAN code: 8429898026169



Main characteristics

- 1/2.7" progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif (S/G/T profile)
- 2.8 to 12mm autofocus motorised lense
- 107° to 34° horizontal viewing angle
- Advanced video analytics (perimeter, line of sight, pedestrian and face detection, crowd and queue detection...)
- Infrared illumination with 45m range
- IP67 protection rating
- Micro SD card slot
- Power-Out function
- Compatible with docking stations C-BASE01 and C-BASE05
- Dimensions: 84(Ø) x 242(D) mm

More information

Visit in the website: <https://golmar.es/products/cip-24b5da>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Bullet IP camera CIP-24B5DA Full color bullet 2.8-12 motorized VA AD 5Mpx



Specifications	
Type	Bullet
Technology	IP
Image sensor	1/2,7" progressive CMOS
Max. Resolution	5Mpx
Images by sec. (FPS)	25
Colour	White
Mounting	Wall
Lense	Motorized
Focal length	2,8 - 12 mm
Zoom (x)	4
Max. Aperture ratio	1,8 - 3,3
Horizontal field of view (°)	107 - 34
Vertical field of view (°)	55 - 19
Minimum illumination (lux)	Color 0.004lux @ F1.6(AGC ON) ; B/N 0 lux @ IR ON
Night vision mode	Full Color
White light distance (m)	45
IR distance max. (m)	45
Autotracking	No
WDR	Yes
AOC	No
Additional functions	AWB,BLC,AES,DNR,3D-DNR
Bitrate	256Kbps ~ 8Mbps
Main Stream (FPS)	25fps @ 5Mpx (2880 x 1620)
Sub Stream (FPS)	25 fps @ 720P(1280x720), VGA(640x480), QVGA(320x240)
Video compression	H.264,H.265
Audio compression	G711, G726
Face recognition	No
Video Analysis	LCD,PID,PD,VD,FD,SOD,CC,CD,QD,HM
Network interface	RJ45
I / O alarms	No
Built-in microphone	Yes
Built-in speaker	Yes
UTC	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Degree of protection (IP)	67
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-35
Relative humidity work (max.)	95%
Input voltage (V)	12Vcc,PoE
Included power supply	No
Rest consumption (W)	3
Max. consumption (W)	9
Dimensions - High (mm)	84
Dimensions - Width (mm)	87
Dimensions - Deep (mm)	242
Weight (gr.)	811
Certifications	CE, RoHS

Accessories

- C-BASE01 high junction box for camera
- C-BASE05 junction box for bullet

Visit in the website: <https://golmar.es/products/cip-24b5da>