

Dome IP camera CIP-21D4D Full color 2.8mm AD 4Mpx



Reference: CIP-21D4D
Product code: 31692052
EAN code: 8429898026190



Main characteristics

- Domo FULL COLOR de 4Mpx con óptica de 2,8mm
- Sensor de 1/3" progresivo CMOS
- Compresión H.265 / H.264
- Protocolo propietario / Onvif
- Óptica fija 2,8mm con ángulo de visión horizontal de 95°
- Iluminación infrarroja con alcance de 25m
- Iluminación luz blanca visible de 20m
- Grado de protección IP67
- Ranura para tarjeta micro SD
- Micrófono y altavoz incorporado
- Luz roja y azul disuasoria
- Compatible con bases de conexión C-BASE01 y C-BASE02
- Dimensiones: 100(Ø) x 90(Al) mm

More information

Visit in the website: <https://golmar.es/products/cip-21d4d>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Dome IP camera CIP-21D4D Full color 2.8mm AD

4Mpx



Specifications	
Type	Dome
Technology	IP
Max. Resolution	4Mpx
Images by sec. (FPS)	25
Colour	White
Mounting	Ceiling
Lense	Fixed
Focal length	2,8 mm
Max. Aperture ratio	F 1,0
Horizontal field of view (°)	95
Vertical field of view (°)	51
Minimum illumination (lux)	Color 0.002 Lux (F1.0,AGC ON) B/W 0 lux @ IR ON
Night vision mode	Day/Night
White light distance (m)	20
IR distance max. (m)	25
Autotracking	No
WDR	No
AOC	No
Additional functions	AWB,BLC,AES,3D-DNR,D-WDR
Bitrate	512Kbps ~ 4Mbps
Main Stream (FPS)	25fps @ 4Mpx (2560x1440)
Sub Stream (FPS)	25fps @ VGA (640x480)
Video compression	H.264,H.265
Face recognition	No
Video Analysis	LCD,PID
Internal storage	Yes (max 256Gb)
Network interface	RJ45
I / O alarms	No
I / O audio	No
Built-in microphone	Yes
Built-in speaker	Yes
UTC	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, SNMP, HTTPS
Compatibility	C-BASE01 and C-BASE02
Degree of protection (IP)	67
Material	Aluminium
Maximum working temperature (°C)	60
Minimum working temperature (°C)	-35
Relative humidity work (max.)	95%
Input voltage (V)	12Vcc,PoE
Included power supply	No
Rest consumption (W)	1.2
Max. consumption (W)	5
Dimensions - Diameter (mm)	100
Dimensions - Deep (mm)	90
Weight (gr.)	312
Certifications	CE, RoHS

Accessories

- Wall mount bracket SP-21P for small dome
- C-BASE01 high junction box for camera
- C-BASE02 high junction box for camera

Visit in the website: <https://golmar.es/products/cip-21d4d>