

Dome IP camera, CIP-124D2E PoE, 2Mpx



Reference: CIP-124D2E
Product code: 31692070
EAN code: 8429898024073



Main characteristics

- 2Mpx PoE dome with 2.8 to 12mm lens
- 1/2.7" progressive CMOS sensor
- H.264 / H.265 compression
- Proprietary protocol / Onvif
- 2.8 to 12mm autofocus motorized lens
- 106° to 35° horizontal angle of view
- Infrared illumination with 40m range
- IP66 protection rating
- Micro SD card slot
- Audio terminals
- Power-Out function
- Compatible with docking station C-BASE02 and C-BASE04
- Dimensions: 135(Ø) x 127(H) mm

More information

Specifications	
Type	Dome
Technology	IP
Max. Resolution	2Mpx
Colour	White
Mounting	Ceiling
Lense	Motorized
Focal length	2.8-12mm
Zoom (x)	4
Night vision mode	Day/Night
IR distance max. (m)	40
WDR	No
Additional functions	AWB,BLC,AES,3D-DNR,D-WDR
Bitrate	128Kbps ~ 4Mbps
Main Stream (FPS)	1080P (1920x1080)
Sub Stream (FPS)	VGA (640x480)
Video compression	H.264,H.265
Internal storage	Yes (max 256Gb)
Network interface	RJ45
I / O alarms	No
I / O audio	1/1
Built-in microphone	No
Built-in speaker	No
Integrated WiFi	No
Remote Access / App	Web,App GolmarView,VMS Pro
Degree of protection (IP)	66
Input voltage (V)	12Vcc,PoE
Included power supply	No
Dimensions - High (mm)	127
Dimensions - Diameter (mm)	135
Certifications	CE,RoHS

Accessories

- C-BASE02 high junction box for camera
- AUDIO-BOX microphone and loudspeaker for CCTV applications
- C-BASE04 high junction box for camera
- SW-104 4-port PoE Switch

Visit in the website: <https://golmar.es/products/cip-124d2e>

Visit in the website: <https://golmar.es/products/cip-124d2e>