

2Mpx IP Dome CIP-21D2E with 2.8mm lense PoE

Reference: CIP-21D2E
 Product code: 31691024
 EAN code: 8429898018478



Main characteristics

- Dome with 2Mpx PoE 2.8mm lens
- 1/2.7" Progressive CMOS Sensor
- H.264 / H.265 compression
- Owner protocol / Onvif 2.6
- Fixed lens 2.8mm / Field of view 103°.
- 18 leds (SMD) / 30m
- Degree of protection IP66
- Dimensions 60(W) x 90(H) x 100(D)mm

Additional information

| | | | |
|-------------------|--|-----------------------|--|
| Resolution | 2MP 1920(H)×1080(V) | Protocols | TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,SMTP,NTP,UPnP,SNMP,HTTPS,FTP, |
| Image Sensor | 1/2.7" Progressive CMOS | System Compatibility | ONVIF(Ver 2.6) |
| Min. Illumination | Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON | Interface | RJ45 10M / 100M Ethernet interface x1 |
| Shutter | 1/5 ~ 1/20000s | Led | 18pcs(SMD) |
| Slow shutter | Support | IR Range | Up to 30m |
| Lens | 2.8 mm H.FOV: 103° | SD storage | no |
| Day & Night | IR cut filter with auto switch | Alarm Trigger | no |
| WDR | Digital WDR | Audio | no |
| Video Compression | H.265/H.264 | Video Output: | no |
| Video bit rate | 256Kbps ~ 8Mbps | Reset Button | no |
| Stream | Dual | PoE | yes |
| | Mainstream (1~25fps) | Water Proof | IP 66 |
| Frame Rate | 1080P(1920x1080), 960P(1280x960), 720P(1280x720) | Power Supply | DC 12V/POE |
| | Substream (1~20fps) | Consumption | ≤ 7W |
| | VGA(640x480),QVGA(320x240) | Dimension | 60x 90x100mm |
| Image Settings: | Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable | Weight | appr. 225g |
| BLC | Support | Storage Temperature | -30 +60°C |
| Privacy Mask | Support | Operating Temperature | -30 +55°C |
| Video Analytics | N/A | | |

Visit in the website: <https://golmar.es/products/2mpx-ip-dome-cip-21d2e-with-28mm-lense-poe>