

4.5" Medium Speed PTZ-20X5IPM ONVIF IP Dome

Reference: PTZ-20X5IPM
 Product code: 31600235
 EAN code: 8429898019376



Main characteristics

- 4.5" Medium Speed PTZ ONVIF IP Dome
- 5MPx 1/3" Sensor
- Compression H.265 / H.264
- Optical zoom x20 (4.7mm-94mm)
- With 6 night vision LEDs
- Degree of protection IP66
- Wall bracket included
- Dimensions Ø136 x 222mm

Additional information

Camera

Sensor	1/3" CMOS 5MP AR0521 (Hi3516D)
Output Pixel	2592x1944/15fps 2592x1520/22fps
Lens	20X f=4.7mm~94mm
Iris	F1.6~F3.0
Min. illumination	Color:0.1Lux B/W:0.01Lux
View of Angle FOV	2.32°~61.2°
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR,3DNR
WDR	DWDR, WDR≥120dB
S/N Ratio	≥50dB

Dome

Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, CMS, Management Platform
Mobile View(optional)	RxCamView App (Needs NVR)
Video compression	H.264/H.265/M-JPEG
Audio compression	G711,PCM

Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Rotation Speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets dwell time 01-60s interval available
A-B scan	User programmable
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
Operating temperature	-40°C~+60°C
Operation menu	English
Power	DC 12V 4A, PoE
Consumption	≤25W
Weight	N.W.:1.56KG/G.W:2.24KG

IR parameters

Auto Control IR LED	PWM
IR distance	Up to 80 meters
LEDs	6PCS Array 42Mil IR LED
Support ambient light detection	IR illumination on 1-9 grades selectable

Visit in the website: <https://golmar.es/products/4-5-medium-speed-ptz-20x5ipm-onvif-ip-dome>