

High Speed ONVIF Dome PTZ-12X5IPT with Autotracking

Reference: PTZ-12X5IPT
 Product code: 31612354
 EAN code: 8429898019451



Main characteristics

- PTZ IP Dome with Auto Tracking System
- 5Mpx resolution
- 120dB WDR System
- Intelligent video analysis
- 4.7-56.4mm (12X) autofocus lens

Additional information

Camera		Gain Control	Auto/Manual
Image Sensor	1/2.8" Progressive Scan CMOS	Noise Reduction	2D/3D DNR
Effective Pixels	2560(H)×1920(V)	Electronic Image Stabilization(EIS)	N/A
Scanning System	Progressive	Digital Zoom	16x
Electronic Shutter	1/5-1/20000s	Motion Detection	Off / On
Min. illumination	Color:0.01Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON)	Audio	
S/N Ratio	55dB	Compression	G.711, RAM_PCM
IR Distance	Smart IR up to 80m	Network	
IR LEDs	6pcs	Ethernet	RJ-45 (10/100Base-T)
Lens		Protocols:	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, APR, SNMP
Focal Length	4.7~56.4mm	Interoperability	ONVIF, CGI
Max. Aperture	F1.6~F3.0	Max. User Access	10 Users
Angle of View	H: 58.13°~6.17°, V: 35.46°~3.65°	Web Viewer	<IE11
Optical Zoom	12x	Interface	
Focus Control	Auto/Manual	Ethernet	I1 Ethernet (10/100 Base-T) RJ-45 Connector
PTZ		Audio Interface	1ch Audio In,1ch Audio Out
Pan/Tilt Range	Pan: 0° ~ 360° endless, Tilt: -10° ~ 90°	Alarm	2ch Alarm In,1ch Alarm Out
Manual Control Speed	Pan: 0.1° ~180° /s, Tilt: 0.1° ~90° /s	RS485	N/A
Preset Speed	Pan: 180° /s, Tilt: 90° /s	General	
Presets	300	Power Supply	DC12V/POE+
Intelligence		Power Consumption	Less than 25W
Auto Tracking Support	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad	Operating Temperature	Starting Temperature: -40°C ~ 60°C (-40°F ~ 140 °F) Working Temperature:-55°C ~ 60°C (-67°F ~ 140 °F)
IVS		Storage Conditions	Less than 90% RH
Video		Ingress Protection	IP66,TVS4000V
Compression	H.265, H.264, MJPEG	Casing	Metal
Streaming Capability	3 Streams	Dimensions	146.6×139.3×218.3mm
Stream / Frame Rate	Stream1: 2560×1920/2048×1536/1280×960 @25/30fps Stream2: D1/VGA/640×360/CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps	Net Weight	1.5Kg
Bit Rate Control	CBR/VBR		
Day/Night	Auto(ICR) / Color / B/W		

Day/Night Auto(ICR) / Color / B/W
Image Enhancement BLC/HLC/WDR (120dB)
White Balance Auto/Tungsten/Fluorescent/Daylight/Shadow/Manual

Visit in the website: <https://golmar.es/products/high-speed-onvif-dome-ptz-12x5ipt-with-autotracking>

Golmar Sistemas de Comunicación S.A.

Silici 13 · 08940 Cornellà de Llobregat (Barcelona) · Tel: +34 934 800 696 · Fax: +34 934 742 404 · golmar@golmar.es · www.golmar.es