

## 3" PTZ IP dome PTZ-04X2IPM for ceiling mount

Reference: PTZ-04X2IPM  
 Product code: 31600234  
 EAN code: 8429898023519



### Main characteristics

- 3" ONVIF PTZ IP dome for ceiling mount
- 2Mpx 1/2,8" Sensor
- Rotation 0 - 355° (H) / 0 - 90° (V)
- Optical zoom x4 (2.8mm-12mm)
- With 4 night vision LEDs
- IP66 protection grade
- Wall mount bracket not included (SP-04P)
- Dimensions Ø130 x 117mm

### Additional information

IR Range	20m	Day / Night mode	Si
Horizontal pan	0°- 355°; 0-80°/s	Conexiones simultáneas	Main stream: 3 users Sub-stream: 5 users
Vertical tilt	0°- 90°, 0-80°/s	Protocols	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP, ARP,DDNS,DNS,P2P
Presets	220	Compatibility	Compatible with HIKVISION platform, XM. NVR via ONVIF 2.4; GB28181
Park function	Yes	Video resolution	Main stream:1920x1080,1280x960,1280x720,720x576,640x480 Sub-stream:640x480,480x360,352x288,320x240,176x144,close MJPEG: 1920x1080,1280x720
Resolution	2MP 1920 H X 1080 V	Video interface	RJ45 network interface, PoE
Sensor	1/2.8" 2.0M Sony 307 CMOS 0.005Lux@F1.2(color mode);0.001Lux@F1.2(night mode);	Power	DC 12V/2A
Illumination	0Lux (IR ON )	Max. Consumption	10W max
S/N	≥50dB AGC OFF	Temp & Humidity working environment	"- 20°C +60°C ≤90% HR
Focal length	2.8mm-12mm, F1.7-F3.0	Protection	TVS3000V, lightning protection, overvoltage protection and transient voltage protection IP66
FOV	113.9°(wide) ~34.1°(tele)°		
BLC	Auto / manual / indoor / outdoor / sodium lamp		
Expositiom	Program mode / Shutter (1/5 - 1/20,000s) / Slow shutter		
Gain control	Auto / manual		
WDR	DWDR ≥73.7dB		
Noise reduction	DNR, 3DNR		
Focus	Auto / manual		

Visit in the website: <https://golmar.es/products/3-ptz-ip-dome-ptz-04x2ipm-for-ceiling-mount>