

2Mpx IP Dome CIP-121D2E with 2.8mm lens, PoE

Reference: CIP-121D2E
 Product code: 31692050
 EAN code: 8429898024066



Main characteristics

- 2.8mm 2Mpx PoE Dome with 2.8mm lens
- 1/2.7" Progressive CMOS sensor
- H.265 / H.264 compression
- Proprietary protocol / Onvif
- 2.8mm fixed optics / 103° field of view
- LED range 30m
- IP66 degree of protection
- SD card slot
- Built-in microphone
- Compatible with C-BASE01 and C-BASE02
- Dimensions Ø100 x 90mm

Additional information

| | |
|------------------------|--|
| Type | Dome |
| Technology | IP |
| Image sensor | 1/2.7" Progressive CMOS |
| Maximum resolution | 2MPx |
| Lense | 2.8mm |
| Minimum illumination | Colour 0.05lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON |
| Day / Night | Auto IR Filter (Day/Night/Auto/Programmed) |
| Max. infrared range | 30m |
| Additional features | WDR, DNR |
| Bitrate | 128Kbps ~ 4Mbps |
| Main Stream | 1080P (1920x1080) |
| Sub Stream | VGA (640x480) |
| Compression | H.265 / H.264 |
| Video analytics | No |
| Internal storage | Yes (Max.128Gb) |
| Network interface | RJ45 (10/100BASE-T) |
| Alarms | No |
| Audio (RCA) | No |
| Built-in microphone | Yes |
| Remote access | Web Browser, GolmarView App, VMS Pro for PC |
| Compatibility | ONVIF |
| Compatible with base | C-BASE01, C-BASE02 |
| Protection rating (IP) | IP66 |
| Material | Aluminium |
| Operating temp. | -30 +60°C HR ≤ 95% |
| Power consumption | 6W |
| Power supply | 12 Vdc / PoE |
| Dimensions | Ø100mm x 90mm |
| Weight | 460g |

Visit in the website: <https://golmar.es/products/cip-121d2e>